

# PRODUCT DATA SHEET

No. 10807

FEBRUARY 2008

## RONSEAL DECKING RESTORER

Ronseal Decking Restorer is ideal for restoring grey, weathered or heavily soiled decking back to its original colour. Once restored decking can be protected using any decking finish.

### INTRODUCTION

Ronseal Decking Restorer's quick and easy to use gel formulation restores decking back to its natural colour in just 15 minutes.

Ronseal Decking Restorer's fast action, low odour, non-acidic formula is safe to use around both plants and lawns.

Surfaces restored by Ronseal Decking Restorer may be protected using Ronseal Decking Seal, Ronseal Decking Oil, Ronseal Decking Stain or Ronseal Decking Shades.

### COMPOSITION

A water based blend of surface active agents with phosphate builders.

### PROPERTIES

Viscosity - Low.  
VOC Content – Minimal (0-0.29% w/v)  
Colour – Colourless.  
Odour – Low, inoffensive.  
Solubility - Miscible with water.

### FIELDS OF APPLICATION

Ronseal Decking Restorer can be used on all types of exterior decking.

### PREPARATION

Remove debris and accumulations of dirt, moss, mould and algae using a stiff brush.

Ensure the surface is bare and that all previous coatings are completely removed prior to application.

Always test an inconspicuous area before general application to ensure the desired result is achieved.

### APPLICATION

Stir well before use. Liberally apply Ronseal Decking Restorer by brush and work into the surface of the deck by thoroughly scrubbing with a stiff bristle brush.

Allow to work for 15 minutes and then re-scrub before rinsing off with clean water. For best results, rinse using a pressure washer, working down the full length of the boards or alternatively use a garden hose. Ensure all residues are completely washed away.

In cases of several weathering a second application may be required.

Allow at least 2 days for decking to thoroughly dry out before the application of any protective coatings.

### COVERAGE

2.5l is sufficient to treat a deck of 20 to 25 square metres.

### CLEANING OF TOOLS

All brushes and equipment should be cleaned immediately after use using plenty of water and detergent. Remove as much product as possible from application equipment before cleaning.

Do not empty undiluted product into drains or watercourses.

### MAINTENANCE

Decking should be inspected on an annual basis and cleaned and/or retreated as appropriate.

Protection with a Ronseal Decking Finish, along with the use of Ronseal Decking Cleaner, will help to maintain the appearance of the deck.

### STORAGE

Ensure that the container is fully re-sealed after use.

Always store and transport in a secure and upright position.

Protect from frost.

The shelf life of the product in airtight containers will be at least 2 years.

### HEALTH AND SAFETY

Observe and follow all warnings and instructions for use shown on the pack.

Avoid contact with the skin and eyes.

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

Use only in well ventilated areas.

Keep out of reach of children.

Protect from frost.

To avoid the risk of spillage always store and transport in a secure and upright position.

Specific health and safety data sheets are available on request.

#### **FLAMMABILITY**

Non-flammable.

#### **SUPPLY**

Obtainable from DIY retailers, paint suppliers and builders merchants.

#### **SIZES**

Obtainable in 2.5 litre resealable containers.

#### **DISPOSAL**

Some local authorities have special facilities for disposal of waste products.

Do not empty undiluted product into drains or watercourses.

#### **LIABILITY**

Whilst these specifications are based on expert technical knowledge and practical experience, we cannot assume responsibility for any work as the ultimate results depend on factors beyond our direct control. Standard codes of painting practice should be followed.

#### **INFORMATION AND SERVICE**

Our Technical Services Department will be pleased to offer specific guidance or provide any further information you may require.

#### **DATA SHEETS**

Data sheets on other Ronseal products are available on request from our Technical Services Department.

Ronseal Ltd. has been registered to BS EN ISO 9000 1994 (Registered Firm No. FM 1669/1).

Ronseal Ltd. operates an Environmental Management System that complies with the requirements of BS 7750:1994, certificate No. EMS 35924.

Ronseal Ltd. has achieved Investors in People certification, (certificate number 59586).

**©RONSEAL LTD.,**  
Thornccliffe Park,  
Chapelton,  
Sheffield.  
S35 2YP

Tel:  
+44 (0114) 240 9469 (Technical Services)  
+44 (0114) 246 7171 (Main Switchboard)

Fax:  
+44 (0114) 245 5629

E. Mail: [enquiry@ronseal.co.uk](mailto:enquiry@ronseal.co.uk)

Website: [www.ronseal.co.uk](http://www.ronseal.co.uk)

Ronseal is a registered trademark of the Sherwin Williams Company.

FEBRUARY 2008. ISSUE 1