

# PRODUCT DATA SHEET

No.10839

FEBRUARY 2008

## RONSEAL HARDWOOD FILLER

Ronseal Hardwood Filler is a one pack wood filler designed to repair minor damage in hardwood doors, windows and garden furniture. It is available in Mid Stain and Dark Stain variants which resist shrinking and cracking.

### INTRODUCTION

Ronseal Hardwood Filler is ideal for repairing minor damage or imperfections in hardwood. The superior quality one pack Wood Filler when dry forms a hard knock resistant finish.

Ronseal Hardwood Filler is available two varieties to match the more commonly used hardwoods. Ronseal Multi-Purpose Wood Filler is ready to stain after 2 hours.

### COMPOSITION

A water based, acrylic polymer incorporating inert fillers, emulsifiers, viscosity modifiers and inorganic pigments as colouring agents.

### PROPERTIES

Appearance – Smooth paste,  
Colour - dependant on individual shade.

VOC Content – Minimal (0-0.29%)

Odour – Low, inoffensive.

### FIELDS OF APPLICATION

Ronseal Hardwood Filler is ideal for use on hardwood doors, windows and garden furniture.

Not suitable for filling the gaps between floor boards.

### APPLICATION PROCEDURE

The wood should be clean and dry. Lightly sand in the direction of the grain.

Apply directly to the damaged area using a suitable knife. Work the filler well in. When filling deeper holes, the Hardwood Filler should be filled in layers of approximately 5mm and allowed to dry between layers. Do not apply in temperatures below 5°C.

Always leave the filler proud of the surface to allow for sanding. Smooth over with a wet knife, prior to drying, to ensure an even finish. Sand smooth and wipe with a damp cloth.

Ronseal Hardwood Filler is designed to be overcoated with Ronseal Quick Drying Woodstain or Ronseal 5 Year Woodstain.

### DRYING TIME

At 20°C Ronseal Hardwood Filler dries in approximately 2 hours. Low temperatures or high humidity will increase drying times.

### CLEANING OF EQUIPMENT

Tools should be washed in water and detergent immediately after use.

### IMPORTANT NOTES

Do not use Ronseal Hardwood Filler in temperatures below 5°C or in areas of high humidity.

Not suitable for filling the gaps between floor boards.

Ronseal Hardwood Filler may accept stains differently to surrounding wood. Fill and finish a small test area to ensure final result is acceptable.

### STORAGE

Store in a cool, dry, well ventilated place away from heat and sources of ignition. Store upright and carefully reseal partly used containers.

The shelf life of the product in airtight containers is 3 years. Protect from frost. Store above 5°C.

### HEALTH AND SAFETY

Observe and follow all warnings and instructions for use shown on the pack.

Keep out of reach of children.

Avoid contact with skin and eyes.

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

After contact with skin, wash immediately with plenty of water.

Specific health and safety data sheets are available on request.

#### **FLAMMABILITY**

Flash point above 61 °C.

Non-flammable product.

#### **SUPPLY**

Obtainable from most D.I.Y. outlets and builders' merchants.

#### **SIZES**

465g resealable tubs.

#### **LIABILITY**

Whilst these specifications are based on expert technical knowledge and practical experience, we cannot assume responsibility for any work as the ultimate result depends on factors beyond our direct control.

#### **INFORMATION AND SERVICE**

Our Technical Services Department will be pleased to offer specific guidance or provide any further information you may require.

#### **DATA SHEETS**

Data sheets on other Ronseal products are available on request from our Technical Services Department.

Ronseal has been registered to BS EN ISO 9000 1994 (Registered Firm No. FM 1669/1).

Ronseal Ltd operate an Environmental Management System that complies with the requirements of BS 7750:1994, Certificate No. EMS 35924.

Ronseal Ltd has achieved Investors In People certification (certificate no. 59586).

**©RONSEAL LTD.,**  
Thornccliffe Park  
Chapelton  
Sheffield  
S35 2YP

**Tel:**  
**+44 (0114) 240 9469**  
**(Technical Services)**  
**+44 (0114) 246 7171**  
**(Main Switchboard)**  
**Fax: +44 (0114) 245 5629**  
**E. Mail: [enquiry@ronseal.co.uk](mailto:enquiry@ronseal.co.uk)**  
**Website: [www.ronseal.co.uk](http://www.ronseal.co.uk)**

Ronseal is a registered trademark of the Sherwin William's Company.

FEBRUARY, 2008  
ISSUE 1