

PRODUCT DATA SHEET

No. 11167

DECEMBER 2001

RONSEAL GARDEN CARE HARDWOOD FURNITURE OIL

Ronseal Hardwood Furniture Oil is designed to protect quality hardwood garden furniture. It may also be used as a maintenance coat for other previously oiled furniture. Ronseal Hardwood Furniture Oil's blend of natural oils and resins penetrates the wood to nourish and feed whilst providing a low sheen waterproof and durable finish.

INTRODUCTION

Ronseal Hardwood Furniture Oil is designed specifically to replace essential oils necessary to help prevent wood from drying. The blend of natural oils and resins provide a flexible, waterproof and durable coating to good quality, hardwood garden furniture.

Ronseal Hardwood Furniture Oil will provide a clear natural, low sheen finish.

COMPOSITION

Ronseal Hardwood Furniture Oil is a blend of resins and pure tung oil in white spirit.

PROPERTIES

Appearance – Low viscosity liquid.
VOC Content - Very High (Greater than 50% w/v)
Odour – Characteristic solvent type.
Immiscible with water.

FIELDS OF APPLICATION

Ronseal Hardwood Furniture Oil can be used over any quality hardwood furniture.

It should be used over bare hardwood or as a maintenance coat over previously oiled furniture.

Not recommended for use on softwoods.

PREPARATION

All previous coatings such as paint, varnish or woodstain should be totally removed (see 'IMPORTANT NOTES').

Lightly sand to remove any loose wood fibres and remove dust, dirt and grease by wiping over with white spirit, allow to dry thoroughly.

APPLICATION

Ensure surface is clean and dry.

Do not apply in wet conditions or if rain is likely before the product has totally dried.

Wearing suitable gloves, apply liberally using a soft, dry, lint free cloth. Work lightly into the grain, wipe off any excess.

Re-apply as necessary once the previous coat has dried. The application of three coats is recommended, allowing 6 hours between coats.

COVERAGE

Coverage will vary dependent upon the porosity of the substrate.

DRYING TIME

Touch dry in 2 hours, allow 6 hours between coats.

Drying times will vary dependent upon prevailing temperatures, humidity and the substrate.

Allow coating to thoroughly dry before subjecting to heavy wear and allow 48 hours before placing soft furnishings in contact with the treated hardwood.

CLEAN UP

WARNING: cloths and soiled rags may self-ignite without warning. Wash out well in warm soapy water before disposal.

Do not store rags contaminated with Hardwood Furniture Oil.

MAINTENANCE

Maintain regularly with a further coat of Ronseal Hardwood Furniture Oil every 3-6 months.

IMPORTANT NOTES

Ronseal Hardwood Furniture Oil provides a lightly tinted transparent finish for exterior hardwood, always test on a small area first to confirm acceptability.

Certain tropical hardwoods have surface characteristics, which may prevent full absorption of coatings or prolong drying times. In general, oil bound woods may prevent adequate adhesion. Washing the surface thoroughly with white spirit, drying thoroughly and pre-testing the Hardwood Furniture Stain on a small area is recommended.

Avoid inhalation of dust when sanding, wear a suitable face mask or employ wet sanding techniques.

Cloths and soiled rags may self ignite without warning. Wash out well in warm soapy water prior to disposal. Do not store rags contaminated with Hardwood Furniture Oil.

STORAGE

Store in a cool, dry, well ventilated place away from heat and sources of ignition. Carefully reseal partly used containers.

Ensure container is fully re-sealed and that child proof closure is working correctly after use.

The shelf life of the product in airtight containers is at least three years.

HEALTH AND SAFETY

Observe and follow all warnings and instructions for use shown on the pack.

Ensure maximum ventilation when applying and during drying.

When applying in confined spaces, wear a face mask designed to prevent inhalation of solvent vapours.

Wear suitable gloves.

Avoid inhalation of dust during preparation by wearing an appropriate face mask.

Avoid contact with skin and eyes.

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

After contact with skin, wash immediately with plenty of water. Keep out of reach of children.

Repeated exposure may cause skin dryness or cracking.

If swallowed seek medical advice immediately and show label.

Specific health and safety data sheets are available on request.

FLAMMABILITY

Flammable product.
Flash Point ~43°C.

SUPPLY

Obtainable from DIY retailers, paint suppliers and builders merchants.

SIZES

Available in 500ml re-sealable containers.

DISPOSAL

Some local authorities have special facilities for disposal of waste paints/varnishes.

Do not empty product into drains or watercourses.

LIABILITY

Whilst these specifications are based on expert technical knowledge and practical experience, we cannot assume responsibility for any work as the ultimate result depends on factors beyond our direct control. Standard codes of painting practice should followed.

INFORMATION AND SERVICE

Our Technical Services Department will be pleased to offer specific guidance or provide any further information you may require.

DATA SHEETS

Data sheets on other Ronseal Products are available on request from our Technical Services Department.

Ronseal Ltd. has been registered to BS EN ISO 9000 1994 (Registered Firm No. FM 1669/1).

Ronseal Ltd. operate an Environmental Management System that complies with the requirements of BS 7750:1994, Certificate No. EMS 35924

Ronseal Ltd. has achieved Investors in People certification, (certificate number 59586).

©RONSEAL LTD.,
Thorncliffe Park,
Chapelton,
Sheffield.
S35 2YP

Tel:
+44 (0114) 240 9469 (Technical Services)
+44 (0114) 246 7171 (Main Switchboard)

Fax:
+44 (0114) 245 5629

E. Mail: enquiry@ronseal.co.uk

Website: www.ronseal.co.uk

Ronseal is a registered trademark of the Sherwin Williams Company.

DECEMBER, 2001. ISSUE 1