

PRODUCT DATA SHEET

No. 10844

February 2006

RONSEAL SPRAYABLE FENCE LIFE FOR USE WITH THE RONSEAL POWER SPRAYER

Ronseal Sprayable Fencelife provides optimum protection to rough sawn garden timber. The wax enriched polymer resin provides an excellent waterproof barrier whilst it's fade resistant pigments provide unrivalled colour performance. This unique formula enables spray application through the Ronseal Power Sprayer, for speedy application along with excellent protective qualities.

INTRODUCTION

Ronseal Sprayable Fence Life is specifically formulated to provide optimum protection and colour performance to rough sawn garden timber fast and effectively. This product is specifically for use with the Ronseal Power Sprayer which provides accurate, consistent coverage and will deliver enough product to treat a fence panel in two minutes

Ronseal Sprayable Fence Life contains a high level of wax for an enhanced water repellent finish which will not crack or flake and will help to prevent rot.

The blend of high quality pigments in Ronseal Sprayable Fence Life provides long lasting protection to the substrate by limiting the damaging effects of UV light.

A one coat application of Ronseal Sprayable Fence Life will transform new or weathered wood however three coats can be applied where a deeper colour is required.

Ronseal Sprayable Fence Life is safe to use with plants and animals and is available in a range of classic colours.

Two coats can be applied for protection up to 5 years.

COMPOSITION

Ronseal Sprayable Fence Life is a vinyl acetate co-polymer incorporating organic and inorganic pigments.

PROPERTIES

Appearance	Structured liquid, light gel.
Odour	Low, typical acrylic.
VOC content	Low (0.30% to 7.99% w/v)
Non-flammable.	
Miscible with water.	

FIELDS OF APPLICATION

Ronseal Sprayable Fence Life is suitable for use on all rough sawn garden timber such as sheds, fences, trellises, gates and pergolas.

It can be applied to bare wood or wood previously stained, weathered, compatible product of a similar colour.

Ronseal Sprayable Fence Life is not suitable for use on smooth planed wood, decking or garden furniture.

For wood in contact with the ground use a suitable wood preserver.

PREPARATION

Ensure wood is clean and dry prior to application.

Remove any dirt, moss, fungal growth and lichen with a stiff brush.

The treatment of a test area to confirm colour suitability is recommended.

APPLICATION

Shake pack thoroughly prior to use and pour the liquid into the tank of the Ronseal Power Sprayer unit. Do not exceed the maximum Fill level.

Secure the lid of the sprayer using the clips and push the power button to turn on the unit.

Stand with the sprayer nozzle approximately 23cm (9 inches) away from the timber and gently squeeze the trigger to begin spraying.

Keep the nozzle a constant distance away from the timber and spray horizontally across the full width of the panel, working down overlap the previous pass by 50%. Ensure that the vertical struts and edges are treated.

Do not apply in wet conditions or if rain is likely before the product dries. Do not apply at temperatures below 10°C or in high humidity.

Ronseal Sprayable Fence Life is designed for use with the Ronseal Power Sprayer see instruction manual for further details.

Do not spray in windy conditions. Use cardboard or plastic to protect from overspray.

Do not apply in damp conditions or if rain is likely before the product is dry.

If over coating strong or contrasting colours, or where additional weathering protection is required, further coats will be necessary.

Ronseal Sprayable Fence Life is safe to use around plants and animals. If plants are splashed during application wipe clean with a damp cloth before the product dries. Pets should be kept away from treated areas until the product has thoroughly dried.

COVERAGE

One 5lt will treat up to 6 fence panel sides.

DRYING TIME

Touch dry in 2 hours.

Absorbency of substrate, low temperatures and high humidity will lengthen the drying time.

CLEANING OF TOOLS

All tools and equipment should be cleaned immediately after use by washing in water and detergent.

Remove as much product as possible from tools and equipment before washing.

Please see Ronseal Power Sprayer instruction manual for further details.

IMPORTANT NOTES

Apply in accordance with the coverage guidelines otherwise product performance will be reduced.

Always test a small area prior to full application to confirm colour suitability and level of adhesion. The final colour will be influenced by the texture, grain, colour, porosity and type of wood as well as the number of coats applied.

Do not apply in temperatures below 10°C or in conditions of high humidity or if rain is likely before the product has fully dried.

Do not use on surfaces treated with solvent based fence treatments unless they have aged for at least one month.

STORAGE

Store in a cool, dry, well ventilated place away from heat and sources of ignition. Carefully reseal partly used containers. Do not store near foodstuffs. Protect from frost.

To avoid risk of spillage, always store and transport in a secure and upright position.

The shelf life of the product in airtight containers is at least three years.

HEALTH AND SAFETY

Observe and follow all warnings and instructions for use shown on the pack.

Avoid contact with skin and eyes.

Do not breathe vapour/spray.

Use only in well ventilated areas.

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

After contact with skin, wash immediately with plenty of soap and water or a proprietary skin cleanser.

Keep out of reach of children.

Ensure container is fully resealed after use.

Specific health and safety data sheets are available on request.

FLAMMABILITY

Non-flammable.
Flash point above 61°C.

SUPPLY

Obtainable from selected DIY retailers.

SIZES

Available in 5 litre re-sealable containers.

DISPOSAL

Some local authorities have special facilities for disposal of waste paints/varnishes.

Do not empty product into drains or watercourses.

LIABILITY

Whilst these specifications are based on expert technical knowledge and practical experience, we cannot assume responsibility for any work as the ultimate result depends on factors beyond our direct control. Standard codes of painting practice should be followed.

INFORMATION AND SERVICE

Our Technical Services Department will be pleased to offer specific guidance or provide any further information you may require.

DATA SHEETS

Data sheets on other Ronseal Products are available on request from our Technical Services Department.

Ronseal Ltd. has been registered to BS EN ISO 9000 1994 (Registered Firm No. FM 1669/1).

Ronseal Ltd. operate an Environmental Management System that complies with the requirements of BS 7750:1994, Certificate No. EMS 35924

Ronseal Ltd. has achieved Investors in People certification, (certificate number 59586).

©RONSEAL LTD.,

**Thorncliffe Park
Chapelton
Sheffield
S35 2YP**

Tel:
+44 (0114) 240 9469 (Technical Services)
+44 (0114) 246 7171 (Main Switchboard)
Fax:
+44 (0114) 245 5629

E. Mail: enquiry@ronseal.co.uk

Website: www.ronseal.co.uk

Ronseal is a registered trademark of the Sherwin Williams Company.

FEBRUARY 2006. ISSUE 1